

JAVS Centro accessories high-definition video switching and routing to new and existing Centro systems



JAVS-MPA

JAV-MPA

The JAVS MPA, or Centro Microphone Pre Amplifier Adaptor can be used for adding microphones or low output audio sources to a JAVS P306 audio mixer. This adaptor can be used for conventional micro-phones (balanced or unbalanced). It uses a 3-pin mini XLR, 3 pin block terminal header connector or standard RJ45 connector for the input. The pre-amp does not allow record lighting or push to mute functionality. The amplifier allows for a +10, 20, 30, or 40 dB boost to the incoming audio. If necessary -internal phantom power can be dis-connected. Internal circuit provides microphone failure detection signal.

Input

- Standard 3 pin mini XLR-F connector
- 3 positions block terminal header 3.81mm
- RJ45 connector Output

Output

Standard RJ45 connector, this connection needs to be a pin to pin connection with the mixer. The current recommendation for this connection is EIA/TIA 568B Standards.

JAV-ATTPRO-RJ45

JAV-ATTPRO-PHX



JAV-ATTPRO-RJ45 / JAV-ATTPRO-PHX

The Attenuation Adaptor can be used to match the audio levels of different devices to ensure compatibility. It offers fixed attenuation of 0, -30, -40, -50 dB. JAVS offers 2 versions of the ATT Pro; JAV-ATTPRO-RJ45 is a RJ45 to 3 pin phoenix connector while JAV-ATTPRO-PHX is a phoenix to phoenix connector. Both attenuators have gal-vanically isolated Input /Output.



JM-14 Flex Microphone Combiner

JM-11 Flex Microphone Combiner

The Centro Microphone expander/combiner can be used to connect multiple microphones to a single microphone input on the Centro. This accessory can be used if there is a need for greater number of microphones, or if multiple microphones are used in any one particular area of a room.

**Note: Using the expander limits the functionality of the JAVS FlexMicrophone.*